



MSDS

MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.

**EASY TEXTURE ORANGEPEEL
& SPLATTER**

ITEM #4091, #4092

HAZARDOUS MATERIAL INFORMATION SYSTEM	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PROTECTIVE EQUIPMENT	I

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME) (I=SAFETY GLASSES, GLOVES, & VAPOR RESPIRATOR)

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:
HOMAX PRODUCTS, INC.
840 WEST HORTON ROAD
BELLINGHAM WA 98226

24 HOUR EMERGENCY PHONE NUMBER:
CHEMTREC 1-800-424-9300

INFORMATION PHONE NUMBER: 1-800-729-9029

DATE OF PREPARATION: 7/30/99

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	OCCUPATIONAL EXPOSURE LIMITS			SPECIES & ROUTE	
		OSHA PEL	ACGIH TLV	%	LD50	LC50
115-10-6	DIMETHYL ETHER PROPELLA	N/A	N/A	500 PPM	N/A	164,000PPM/4HR RAT INHA

*** NO TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR:	WHITE/SLIGHT ETHEREAL ODOR
BOILING POINT:	-13 DEG F.
VAPOR DENSITY:	HEAVIER THAN AIR
WATER SOLUBILITY %:	SOLUBLE IN WATER
EVAPORATION RATE:	FASTER THAN n-BUTYL ACETATE
SPECIFIC GRAVITY (WATER = 1)	0.9
MATERIAL V.O.C.	1.06 LBS/IMP GAL 0.88 LBS/US GAL 106 GMS/LTR
FREEZING POINT:	32 F. pH: N/A
COEFFICIENT OF WATER/OIL DIST:	N/A
ODOR THRESHOLD:	N/A

N/E = NOT ESTABLISHED

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: < 0 DEG F. METHOD USED: TOC.
FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER: 3.4%
UPPER: 18.0%
UNIFORM FIRE CODE STANDARD 88-1 LEVEL 1 AEROSOL
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES:

KEEP CONTAINER COOL WITH WATER SPRAY OR FOG, UNTIL FIRE HAS BEEN EXTINGUISHED

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF PRESSURE FROM EXTREME HEAT OR FIRE.

FLAMMABILITY - T.D.G.R. CLASS CLASS ORM-D CONSUMER COMMODITY, (UN1950 CLASS 9)
SENSITIVITY TO IMPACT: DO NOT PUNCTURE
SENSITIVITY TO STATIC DISCHARGE: PRIMARILY VAPORS

SECTION V - REACTIVITY DATA

STABILITY:

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID

HIGH TEMPERATURES

INCOMPATIBILITY (MATERIALS TO AVOID):

STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS:

IF HEATED WITH PEROXIDES PRESENT, VIOLENT DECOMPOSITION CAN OCCUR

SECTION VI - HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION: YES SKIN: YES

HEALTH HAZARDS (ACUTE AND CHRONIC):

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT, OR NERVOUS SYSTEM
DEPRESSION - CHARACTERIZED BY HEADACHE, DIZZINESS, NAUSEA, OR POSSIBLE UNCONSCIOUSNESS.
SKIN OR EYE CONTACT: PRIMARY IRRITATION. PROLONGED OR REPEATED CONTACT TO SKIN MAY
CAUSE DERMATITIS - EXERCISE DUE CARE.

INHALATION:

MAY CAUSE DIZZINESS OR NAUSEA.

SKIN ABSORPTION:

MAY CAUSE IRRITATION OR BURNING SENSATION.

SKIN AND EYE CONTACT:

MAY CAUSE IRRITATION OR BURNING SENSATION.

INGESTION: N/A

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO
THIS PRODUCT DOES NOT CONTAIN ANY RECOGNIZED CARCINOGEN.

OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES

VAPORS: REMOVE FROM EXPOSURE AND RESTORE BREATHING, SEEK MEDICAL ATTENTION.

SPLASH: (SKIN) WASH AFFECTED AREA, REMOVE CONTAMINATED CLOTHING, SEE PHYSICIAN IF ANY IRRITATION PERSISTS.

SPLASH: (EYES) FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES AND TAKE TO A PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION: FLAMES, SPARKS, STATIC ELECTRICITY & ELECTRICAL. VENTILATE AREA AND SOAK UP WITH INERT ABSORBENT USING NON-SPARKING TYPE TOOLS.

WASTE DISPOSAL:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

DO NOT STORE ABOVE 120 DEG. F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAME.

OTHER PRECAUTIONS:

DO NOT GET IN EYES. DO NOT BREATHE VAPORS. AVOID SKIN CONTACT. DO NOT TAKE INTERNALLY. SMOKING WHILE USING THIS PRODUCT MUST BE STRICTLY PROHIBITED. IN ADDITION TO ALL OTHER HAZARDS AND PRECAUTIONS - DUST FROM SANDING THE DRY PAINT FILMS SHOULD BE TREATED AS A NUISANCE DUST WITH A TLV OF 10mg/cubic meter.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION:

OUTDOORS: APPROVED MECHANICAL PARTICULATE FILTER TO REMOVE AIRBORNE OVERSPRAY IN RESTRICTED AREAS WITH POOR VENTILATION USE NIOSH APPROVED ORGANIC CARTRIDGE RESPIRATOR.

VENTILATION:

ALL APPLICATION AREAS SHOULD BE ADEQUATELY VENTILATED IN ORDER TO KEEP THE INGREDIENTS IN SECTION II BELOW THEIR EXPOSURE LIMITS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.

EYE PROTECTION:

SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

EYES - WASH FOUNTAIN AND SAFETY SHOWER.
REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.

WORK/HYGIENIC PRACTICES:

AVOID PROLONGED OR REPEATED CONTACT. DO NOT BREATHE VAPORS.

SECTION IX - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX PRODUCTS, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HERewith.